

Fig. 1




Fig. 2A

2/20




Fig. 2B




Fig. 2C





Fig. 3

5/20



400



Fig. 5

7/20

500

# MULTI-OPERATING SYSTEMS WITH SHARED I/O




Fig. 6

## MULTI-OPERATING SYSTEMS WITH SHARED ETHERNET CONTROLLER






Fig. 7

9/20




Fig. 8

10/20

MULTI-OPERATING SYSTEMS WITH SHARED OTHER CONTROLLER




Fig. 9




Fig. 10





Fig. 11



- PI Protocol ID Field
- OSD OS Domain Number
- RN Resource Number (which buffer the packet belongs to)
- R reserved

Fig. 12 (Prior art)




Fig. 13

13/20




Fig. 14

1400

MULTI-OPERATING SYSTEMS WITH SHARED ETHERNET CONTROLLER  
PACKET FLOW EXAMPLE




Fig. 15

15/20

METHOD OF SHARED I/O DOWNSTREAM TRANSMISSION FROM SWITCH




Fig. 16

16/20

METHOD OF SHARED I/O UPSTREAM TRANSMISSION TO SWITCH






Fig. 17

## METHOD OF SHARED I/O DOWNSTREAM TRANSMISSION TO ENDPOINT




Fig. 18

18/20

METHOD OF SHARED I/O UPSTREAM TRANSMISSION FROM ENDPOINT





Fig. 19

1900

MULTI-OPERATING SYSTEMS WITH SHARED I/O




+

Fig. 20

20/20

2000

8 BLADE REDUNDANT ARCHITECTURE WITH SHARED I/O SWITCHES AND ENDPOINTS



+